

## U1P-Bike - 4T Full Synthetic Motor Oil

# SAE 5W-40 API SN, JASO MA2

Motorcycle – ATV | United States

### Product Description

Ultra 100% synthetic 4-Stroke engine oil. Top performance formula that meets and exceeds the highest industry standard JASO MA2 API SN specifications. Top technology 100 % synthetic base-stock with precisely balanced Ultra high-performance additive package. Allow maximum power delivery by reducing internal friction for exceptional wear protection, Increasing engine life for on-road, off-road, street or motorsports. Proven at extreme temperature racing conditions, speed, and endurance.



### Features and Benefits

- For all 4-stroke motorcycles and ATVs with or without catalytic converters.
- For engines with or without integrated gear box, transmission. Wet or dry clutch.
- JASO MA2 API SN ensures optimum clutch performance at start-up, acceleration, and full speed.
- Exceptional wear protection extending engine, gear box and clutch life, leading to reduced maintenance cost.
- For liquid cooled or air-cooled engines. Improves thermal stability and fuel efficiency.
- Improved high temperature deposit protection for engine cleanliness and minimum sludge build up.
- Reduces oil thickening facilitating extended oil life, inside the manufacturer's oil change interval recommendation.
- Smoother shifting and enhanced clutch feeling and precision.



## Product Code

| Presentation    | SKU             | Manufacture ID | UPC          |
|-----------------|-----------------|----------------|--------------|
| 5 Gallon Pail   | UFS05404TSNMA2P | UL408          | 810050652322 |
| 55 Gallon Drum  | UFS05404TSNMA2D | UL408          | 810050652315 |
| 265 Gallon Tote | UFS05404TSNMA2T | UL408          | 810050652308 |

## This product meets or exceeds the requirements of

API SN  
JASO MA2

## Properties and Specifications\*

| Parameter                              | Result        |
|----------------------------------------|---------------|
| Appearance                             | Amber, liquid |
| Viscosity @ 40°C, cSt, ASTM D445       | 84.5          |
| Viscosity @ 100°C, cSt, ASTM D445      | 14.5          |
| Viscosity index, ASTM D2270            | 180           |
| CCS Apparent Viscosity, cP, ASTM D5293 | 6,000@-30°C   |
| MRV Apparent Viscosity, cP, ASTM D4684 | 24,000@-35°C  |
| Pour point, °C, ASTM D97               | -42           |
| Flash point, °C, ASTM D92              | 215           |

\*Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

Revised: 03/06/2023