

U1P-Ride 4T Full Synthetic Motor Oil

20W-50 API SJ, JASO MA2, V-TWIN

MotorCycle – ATV | United States

Product Description

Ultra 100% synthetic 4-Stroke engine oil. Top performance formula that meets and exceeds the highest industry standard JASO MA2 API SJ specifications. Top technology 100 % synthetic base-stock with precisely balanced Ultra high-performance additive package. Allow maximum power delivery by reducing internal friction for exceptional wear protection, Increasing engine life for on-road, off-road, street or motorsports. Proven at extreme temperature racing conditions, speed, and endurance.



Features and Benefits

- For all 4-stroke motorcycles and ATVs with or without catalytic converters.
- For engines with or without integrated gear box, transmission. Wet or dry clutch.
- JASO MA2 API SJ ensures optimum clutch performance at start-up, acceleration, and full speed.
- Exceptional wear protection extending engine, gear box and clutch life, leading to reduced maintenance cost.
- For liquid cooled or air-cooled engines. Improves thermal stability and fuel efficiency.
- Improved high temperature deposit protection for engine cleanliness and minimum sludge build up.
- Reduces oil thickening facilitating extended oil life, inside the manufacturer's oil change interval recommendation.
- Smoother shifting and enhanced clutch feeling and precision.



Product Code

Presentation	SKU	Manufacture ID	UPC
5 Gallon Pail	UFS20504TVTSJMA2P	UL413	810050652629
55 Gallon Drum	UFS20504TVTSJMA2D	UL413	810050652612
265 Gallon Tote	UFS20504TVTSJMA2T	UL413	810050652605

This product meets or exceeds the requirements of

API SJ

JASO MA2

Properties and Specifications*

Parameter	Result
Appearance	Amber, liquid
Viscosity @ 40°C, cSt, ASTM D445	172.15
Viscosity @ 100°C, cSt, ASTM D445	20.5
Viscosity index, ASTM D2270	140
CCS Apparent Viscosity, cP, ASTM D5293	5,800@-15°C
MRV Apparent Viscosity, cP, ASTM D4684	18,000@-20°C
Pour point, °C, ASTM D97	-30
Flash point, °C, ASTM D92	225

*Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

Revised: 03/06/2023