

U1P-Duty - Synthetic Blend Motor Oil

SAE 10W-40 Euro Rennsport, ACEA E6/E7/E9, API CK-4

Heavy-Duty – On-Highway | United States

Product Description

U1P-DRIVE SAE 10W-40 Euro Rennsport Synthetic Blend Motor Oil, ACEA E6/E7/E9, API CK-4, is a high-performance, low SAPS (sulfated ash, phosphorus, sulfur) heavy-duty diesel engine oil recommended for extended drain applications requiring ACEA E6/E7/E9 or API CK-4 performance. This top-tier synthetic blend engine oil is engineered for high-performance luxury European vehicles, formulated with pure full synthetic base stock combined with 100% virgin mineral base stocks and an ultra-premium additive package.



U1P-DRIVE Euro Rennsport Synthetic Blend Motor Oil meets and exceeds the rigorous demands of Euro ACEA E6/E7/E9 performance requirements, offering outstanding oxidation and thermal stability, shear stability, wear protection, detergency, dispersancy, and protection against low-speed pre-ignition. It provides superior engine protection and performance for modern European vehicles, ensuring optimal operation under challenging conditions.

Features and Benefits

- Longer engine life.
- Excellent overall lubrication and wear protection even in extreme driving conditions.
- Provides excellent cold start lubrication and reduces friction for better gas millage and control of emissions.
- Prevents the formation of varnishes, sludge and deposits that could be generated at high temperatures.
- Maximum protection against corrosion and rust formation.
- Reduces lubricant evaporation at high temperatures.
- Outstanding stable performance within the maximum oil change interval recommended by the vehicle's manufacturer.

This product meets or exceeds the requirements of:

API CK-4, CJ-4
Caterpillar ECF-3
Cummins CES 20086, 20081
Detroit Diesel DFS 93K218
Deutz DQC IV-10 LA
MB 228.31, 228.51
MTU Type 3.1
Volvo VDS 4.5

Properties and Specifications*

Parameter	Result
Appearance	Amber, liquid
Viscosity @ 40°C, cSt, ASTM D445	97.8
Viscosity @ 100°C, cSt, ASTM D445	14.6
Viscosity index, ASTM D2270	155
CCS Apparent Viscosity, cP, ASTM D5293	6,260 @ -25°C
MRV Apparent Viscosity, cP, ASTM D4684	26,600 @ -25°C
Pour point, °C, ASTM D97	-33
Flash point, °C, ASTM D92	228
Sulfated Ash, %wt, ASTM D874	1.0

*Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

Revised: 01/15/2025