

U1P-Drive Full Synthetic Motor Oil

5W-30 Euro Rennsport ACEA A3/B4-21

Auto – Light Truck | United States

Product Description

U1P-DRIVE Euro Rennsport Full Synthetic SAE 5W-30, ACEA A3/B4-21 is a top-tier full synthetic engine oil engineered for high-performance luxury European vehicles. Formulated with pure full synthetic base stock combined with an Ultra-premium additive package. This oil is designed for use in fuel injected, turbocharged, supercharged, and carbureted high performance European gasoline and diesel engines. Euro Rennsport Full Synthetic Motor Oil meets and exceeds the rigorous demand of Euro ACEA A3/B4-21 performance requirement. Also, suitable to substitute previous oil specifications recommended for older vehicles.

U1P-DRIVE Euro Rennsport Full Synthetic Motor Oil exhibits outstanding oxidation and thermal stability, shear stability, wear protection, detergency, dispersancy as well as protection against low-speed pre-ignition.

Features and Benefits

- Longer Engine life.
- Excellent overall lubrication and wear protection even in extreme driving conditions.
- Provides excellent cold start lubrication and reduces friction for better gas millage and control of emissions.
- Prevents the formation of varnishes, sludge and deposits that could be generated at high temperatures.
- Maximum protection against corrosion and rust formation.
- Reduces lubricant evaporation at high temperatures.
- Outstanding stable performance within the maximum oil change interval recommended by the vehicle's manufacturer.



Product Code

Presentation	SKU	Manufacture ID	UPC
1.05 QT / 1 Liter	UFS0530AA3B421L	UL116L	810111114431
5 Gallon Pail	UFS0530AA3B421P	UL116P	810111114622
55 Gallon Drum	UFS0530AA3B421D	UL116D	810111114639
265 Gallon Tote	UFS0530AA3B421T	UL116T	810111114646



This product meets or exceeds the requirements of:

ACEA A3/B4-21	Ford WSS-M2C 962-A1
ACEA A3/B3-21	Opel / GM-LL-A-025
BMW Long-Life-01	Opel / GM-LL-B
BMW Long-Life-04	Opel / GM-LL-B-025
Daimler MB 229.3	PSA B71 2296
Daimler MB 220.31	Renault RN0700/710
Daimler MB 229.5	Volkswagen VW 502 00
Daimler MB 229.51	Volkswagen VW 505 00

Properties and Specifications*

Parameter	Result
Appearance	Amber, liquid
Viscosity @ 40°C, cSt, ASTM D445	62.0
Viscosity @ 100°C, cSt, ASTM D445	11.0
Viscosity index, ASTM D2270	171
CCS Apparent Viscosity, cP, ASTM D5293	4,800@-30°C
Pour point, °C, ASTM D97	-42
Flash point, °C, ASTM D92	215

*Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

Revised: 03/06/2023