

U1P-Drive Full Synthetic Transmission Fluid

ATF Euro Rennsport MB15

Transmission | United States

Product Description

U1P-DRIVE Euro Rennsport Full Synthetic ATF MB15 is a premium 100% synthetic automatic transmission fluid formulated with an Ultra high performance additives package, developed to fit Mercedes passenger cars, SUVs, and light duty utility vehicles automatic transmissions for which MB-Approval 236.15 specification is required. Especially recommended for use in all Mercedes vehicles fitted with the 7 speed automatic transmissions (since 2010). Provides enhanced fuel economy and advanced anti-wear properties to protect bearings, bushing and compact heavily loaded gears ensuring a consistent and smooth shifting performance, even under extreme driving conditions.



Features and Benefits

- Premium synthetic ATF that can be used in new model European automatic transmission cars.
- Advance anti wear properties, enhanced friction coefficient and foam control additive for smooth shifting and maximum torque transmission.
- Improved lubrication film strength, high temperature stability and corrosion resistance to extend transmission life and improved fuel economy by reducing gear friction.
- Resistant to oil oxidation and degradation minimizing the formation of lacquers, sludge, and other harmful deposits.
- Compatible with gaskets, rubber parts, plate seals, discs made with elastomers and other seal materials.
- Outstanding low temperature fluidity and anti-shudder performance to avoid vibrations.

Meets and Exceeds:

MB 236.15

Suitable for Use:

Mercedes-Benz C250	Mercedes-Benz G550	Mercedes-Benz ML350
Mercedes-Benz C300	Mercedes-Benz G550 4x4	Mercedes-Benz ML400
Mercedes-Benz C350	Mercedes-Benz G63 AMG	Mercedes-Benz ML550
Mercedes-Benz C400	Mercedes-Benz G65 AMG	Mercedes-Benz ML63 AMG
Mercedes-Benz C450 AMG	Mercedes-Benz GL350	Mercedes-Benz R350
Mercedes-Benz C63 AMG	Mercedes-Benz GL450	Mercedes-Benz S350
Mercedes-Benz C63 AMG S	Mercedes-Benz GL550	Mercedes-Benz S400
Mercedes-Benz CL550	Mercedes-Benz GL63 AMG	Mercedes-Benz S550
Mercedes-Benz CL63 AMG	Mercedes-Benz GLE300d	Mercedes-Benz S63 AMG
Mercedes-Benz CLS400	Mercedes-Benz GLE350	Mercedes-Benz S65 AMG
Mercedes-Benz CLS550	Mercedes-Benz GLE63 AMG	Mercedes-Benz SL400
Mercedes-Benz CL63 AMG	Mercedes-Benz GLE63 AMG S	Mercedes-Benz SL550
Mercedes-Benz CLS63 AMG S	Mercedes-Benz GLK250	Mercedes-Benz SL63 AMG
Mercedes-Benz E250	Mercedes-Benz GLK350	Mercedes-Benz SL65 AMG
Mercedes-Benz E350	Mercedes-Benz GLS63 AMG	Mercedes-Benz SLK250
Mercedes-Benz E400	Mercedes-Benz Maybach S600	Mercedes-Benz SLK350
Mercedes-Benz E550	Mercedes-Benz Maybach S650	Mercedes-Benz SLK55 AMG
Mercedes-Benz E63 AMG	Mercedes-Benz Metris	Sprinter 2500 906 Sprinter
Mercedes-Benz E63 AMG S	Mercedes-Benz ML250	MB 236.1

Properties and Specifications*

Parameter	Result
Appearance	Blue, Dyed Liquid
Density at 20°C (68°F) ASTM D1298	0.84
Viscosity at 40°C (104°F) ASTM D445	19 mm ² /s
Viscosity at 100°C (212°F) ASTM D445	4.4 mm ² /s
Viscosity index, ASTM D2270	149.0
Pour point, °F, ASTM D97	-50.0 °F
Flash point, °F, ASTM D92	378.0 °F

*Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

Revised: 03/06/2023