

U1P-Drive - Full Synthetic Motor Oil

SAE 0W-20 Euro Rennsport ACEA C5/C6, API SP

Auto – Light Truck | United States

Product Description

U1P-DRIVE Euro Rennsport Full Synthetic SAE 0W-20, ACEA C5/C6, API SP is a top-tier full synthetic engine oil engineered for high-performance luxury European vehicles. Formulated with pure full synthetic base stock combined with an Ultra-premium additive package. This oil is designed for use in fuel injected, turbocharged, supercharged, and carbureted high performance European gasoline and diesel engines. Euro Rennsport Full Synthetic Motor Oil meets and exceeds the the rigorous demands of Euro ACEA C5 and ACEA C6 and American API SP and ILSAC GF-6 performance requirements. Also, suitable to substitute previous oil specifications recommended for older vehicles.

U1P-DRIVE Euro Rennsport Full Synthetic Motor Oil exhibits outstanding oxidation and thermal stability, shear stability, wear protection, detergency, dispersancy as well as protection against low-speed pre-ignition.

Features and Benefits

- Excellent overall lubrication and wear protection even in extreme driving conditions.
- Provides excellent cold start lubrication and reduces friction for better gas millage and control of emissions.
- Prevents the formation of varnishes, sludges and deposits that could be generated at high temperatures.
- Maximum protection against corrosion and rust formation.
- Reduces lubricant evaporation at high temperatures.
- Outstanding stable performance within the maximum oil change interval recommended by the vehicle's manufacturer.



Product Code

Presentation	SKU	Manufacture ID	UPC
QT	UFS020SPC5C6L	UL115L	810111114424
JUG (5 QTS)	UFS020SPC5C6J	UL115J	810111116312
5 Gallon Pail	UFS020SPC5C6P	UL115P	810111114592
55 Gallon Drum	UFS020SPC5C6D	UL115D	810111114608
265 Gallon Tote	UFS020SPC5C6T	UL115T	810111114615



This product meets or exceeds the requirements of:

ACEA C5/C6	Land Rover STJLR.03.500677
BMW Longlife-17 FE+	MB-229.71
BMW Longlife-01	MB-229.72
BMW Longlife-04	Opel OV 040 1547 - A20
Chrysler MS-12145	PSA B71 2296
Daimler MB 229.3	Volkswagen VW50200
Daimler MB 229.5	Volkswagen VW50500
Fiat 9.55535-GSX	Volkswagen VW50800
Ford WSS-M2C 947-B1	Volkswagen VW50900
ILSAC GF-6A	VW TL 525
Jaguar	



Properties and Specifications*

Parameter	Result
Appearance	Amber, liquid
Viscosity @ 40°C (104°F), cSt, ASTM D445	41.4 mm ² /s
Viscosity @ 100°C (212°F), cSt, ASTM D445	8.2 mm ² /s
Viscosity index, ASTM D2270	177.0
CCS Apparent Viscosity, cP, ASTM D5293	5,800@-35°C
Pour point, °C, ASTM D97	-48.0°C / 428.0°F
Flash point, °C, ASTM D92	220.0°C / -54.0°F

*Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

Revised: 03/06/2023