

U1P-Drive - Conventional Motor Oil

SAE 10W-30 API SL

Auto – Light Truck | United States

Product Description

U1P-DRIVE SAE 10W-30 Motor Oil, API SL is a high-performance multigrade motor oil formulated for gasoline engines, combining 100% virgin mineral base stocks with an Ultra-premium high performance additive package. This oil is designed for use in carbureted and fuel injected gasoline engines in both normal and high demanding operating conditions.

U1P-DRIVE SAE 10W-30 Motor Oil, API SL exceeds the performance requirements of API SL quality certification. Delivers engine protection and durability. Recommended for on-road and off-road use, light duty and heavy duty. Creates a reliable lubricant film in both cold and hot weather. Excellent for American, European, and Asian gasoline engines that require API SL quality motor oil and previous certifications. Substitutes older API (SJ, SH, SG, SF, SE, SD, SC, SB, SA).

Features and Benefits

- Longer Engine life.
- Excellent overall lubrication and wear protection even at extreme driving conditions.
- Provides excellent cold start lubrication and reduces friction for better gas millage and control of emissions.
- Prevents the formation of varnishes, sludges and deposits that could be generated at high temperatures.
- Maximum protection against corrosion and rust formation.
- Reduces lubricant evaporation at high temperatures.
- Outstanding stable performance within the maximum oil change interval recommended by the vehicle's manufacturer.



Product Code

Presentation	SKU	Manufacture ID	UPC
QT	UC1030SLL	UL301	810050651141
1 US Gallon	UC1030SLG	UL301	810050651134
5 Gallon Pail	UC1030SLP	UL301	810050651127
55 Gallon Drum	UC1030SLD	UL301	810050651110
265 Gallon Tote	UC1030SLT	UL301	810050651103



This product meets or exceeds the requirements of:

API SL

Properties and Specifications*

Parameter	Result
Appearance	Amber, liquid
Viscosity @ 40°C, cSt, ASTM D445	72.38
Viscosity @ 100°C, cSt, ASTM D445	10.75
Viscosity index, ASTM D2270	137
CCS Apparent Viscosity, cP, ASTM D5293	6,510@-25°C
MRV Apparent Viscosity, cP, ASTM D4684	18,200@-30°C
Pour point, °C, ASTM D97	-48
Flash point, °C, ASTM D92	237



*Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

Revised: 04/02/2025