

U1P-Duty – COMPRESSOR OIL GIII ISO VG 150

Heavy-Duty | United States

Product description

Formulated with synthetic API Group III base oils plus a premium performance additive package, **Ultra1Plus™ COMPRESSOR OIL GIII ISO VG 150** provides excellent protection against rust and oxidation while also exhibiting excellent demulsibility and high resistance to emulsification. **Ultra1Plus™ COMPRESSOR OIL GIII ISO VG 150** can reduce downtime and extend drain intervals as the oil's high level of thermal stability prevents sludging and varnishing. Furthermore, the product's excellent ability to shed water as well as the product's resistance to foaming and air entrainment, provide the highest degree of lubrication essential to the demanding requirements of screw air compressors.



Features and benefits

- Protect against corrosion.
- Resistance to foaming.
- Perfect for use in high and low temperatures.
- Increases effectiveness.
- Very good air release.
- Water separation.



Suitable for use

- Screw air compressors.

Technical information*

Parameter*	Test/Method	VG 150
Density @ 15 °C, g/cm3	ASTM D 4052	0.88
Viscosity @ 40°C, cSt	ASTM D445	150.0
Viscosity @ 100°C, cSt	ASTM D445	21.0
Viscosity index	ASTM D2270	165
Pour point, °C (°F)	ASTM D97	-35 (-31)
Flash point, °C (°F)	ASTM D92	235 (455)



*Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

Revised: 03/06/2023