

U1P-Duty - Conventional Motor Oil

SAE 40 API SN/CF

Heavy-Duty | United States of America

Product Description

Is designed to protect high-speed, four-stroke, naturally aspirated, turbocharged and direct injection Heavy Duty gasoline engines requiring API SN and naturally aspirated and turbocharged diesel engines in which API CF service category is recommended, providing stable wear protection, improved control of oil consumption and piston deposits. Formulated for Heavy Duty and Medium Duty engines operating under severe climatic conditions, using a range of fuels including those with more than 0.5% sulfur, also compatible for models asking for API CD and CE or API SM, SJ, and SF. Formulated with 100% virgin paraffinic base stock combined with an Ultra-premium additive package, this oil contains anti-wear, antioxidant, anti-foaming, detergent, and dispersant agents, delivering strong lubricant film performance and high temperature viscosity stability for anti-wear protection in a wide range of heavy-duty applications.

U1P-DUTY SAE 40 Heavy-Duty Motor Oil, API SN/CF protects the engine rings for maximum combustion compression and minimal engine wear, minimizes valve and piston crown deposits, and the Ultra-anti-wear additive protects the valve train and other highly loaded parts. The viscosity index improver additive ensures excellent film protection in hot engine areas.

Features and Benefits

- Improves engine efficiency, protection, and durability.
- Fits diesel and gasoline engines.
- Controls high-temperature oxidation and deposits.
- Maximum performance and protection at high temperatures.
- Saves fuel, reduces heat, and minimizes oil consumption.
- Cleans key engine components.
- Fully compatible if previously used Synthetic, Synthetic blend or conventional oils.
- Hot temperature stable performance for continuous protection throughout the recommended oil service interval.



Product Code

Presentation	SKU	Manufacture ID	UPC
1 US Gallon	UC40SNCFG	UL310	810050651677
5 Gallon Pail	UC40SNCFP	UL310	810050651660
55 Gallon Drum	UC40SNCFD	UL310	810050651653
265 Gallon Tote	UC40SNCFT	UL310	810050651646

This product meets or exceeds the requirements of:

API SN

API CF

Properties and Specifications*

Parameters	Result
Appearance	Amber, liquid
Viscosity @ 40°C, cSt, ASTM D445	127.6
Viscosity @ 100°C, cSt, ASTM D445	13.0
Viscosity index, ASTM D2270	95
Pour point, °C, ASTM D97	-5
Flash point, °C, ASTM D92	195

*Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

Revised: 05/13/2025