

U1P-Duty - Full Synthetic Transmission Fluid

SAE 75W-80 HEAVY-DUTY, API GL-4

Transmission | United States

Product Description

U1P-DRIVE SAE 75W-80 Synthetic HD Transmission Fluid is a premium grade, full synthetic, heavy-duty transmission fluid formulated for optimal performance in Volvo iShift and Mack mDrive® transmissions. This product contains a sophisticated additive system which provides synergistic benefits when combined with synthetic base oils to provide outstanding extended drain capabilities, extreme pressure protection, and exceptional oxidative and thermal stability. Further, this product is extremely shear stable and with optimized frictional characteristics for the recommended applications.

Features and Benefits

- Extended gear and bearing life due to minimal deposits.
- Longer seal life.
- Increased load-carrying capability.
- Contribution to reduced maintenance costs and longer equipment life.
- Helps to reduce operating costs.

Product Code

Presentation	SKU	Manufacture ID	UPC
5 Gallon Pail	UFS7580GL4P	UL508	810050657532



This product meets or exceeds the requirements of:

API GL-4
MAN 341 Type E4
Volvo 97305
Volvo 97307
Volvo 97318

Properties and Specifications*

Parameter	Result
Appearance	Amber, liquid
Viscosity @ 40°C, cSt, ASTM D445	54
Viscosity @ 100°C, cSt, ASTM D445	9.1
Viscosity index, ASTM D2270	150
Pour point, °C, ASTM D97	-55
Flash point, °C, ASTM D92	225

*Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

Revised: 03/28/2025