

U1P-Gear - Conventional Gear Oil

EP ISO 150

Industrial | United States

Product Description

U1P-Gear EP ISO 150 Gear Oil is formulated combining 100% virgin mineral base stocks with an Ultra-premium high performance additive package specially designed to impart enhanced film strength.

These specialty anti-scuffing compounds, which provide advanced protection and lubricity in extreme pressure conditions, consist of sulfur-phosphorous based EP technology for modification of gear rubbing surfaces to prevent welding and galling from inadequate film strength.

Furthermore, U1P-Gear EP ISO 150 Gear Oil is formulated to resist and provide extra protection against rust, oxidation, foaming, moisture, and varnish.

Features and Benefits

- Inhibit rust and corrosion.
- Long equipment life.
- Extreme pressure protection.
- Excellent dispersant properties.
- Excellent lubrication flow characteristics over very wide temperature ranges.
- Protection from galling, scuffing, and welding of gear teeth.
- Non-corrosive to bronze, brass, copper, and other copper alloy parts.



Product Code

Presentation	SKU	Manufacture ID	UPC
5 Gallon Pail	UC150EPP	UL712	810050654661
55 Gallon Drum	UC150EPD	UL712	810050654654
265 Gallon Tote	UC150EPT	UL712	810050654647

This product meets or exceeds the requirements of:

Recommended for the lubrication of slides, ways, sprockets, chain drives, winches, hoists, and machine tools. Additionally, U1P-Gear EP ISO 680 Gear Oil meet the following performance requirements:

AGMA 9005-E02 EP
DIN 51517-3
Cincinnati Machine (Gear C Series)
US Steel 224
ISO 12925-1 CKC/CKD
GM LS-2

Technical information*

Parameter	Result
Appearance	Amber, liquid
Viscosity @ 40°C, cSt, ASTM D445	145.7
Viscosity @ 100°C, cSt, ASTM D445	15.31
Viscosity index, ASTM D2270	107
Pour Point, °C	-27°C (-17°F)
Flash Point, °C	>220

*Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

Revised: 03/06/2023