

U1P-Duty Conventional Hydraulic Oil

SAE 10W, TO-2

Industrial | United States

Product Description

Formulated with high viscosity-index paraffinic base stocks and premium performance additives, U1P-DUTY SAE 10W Hydraulic Oil, TO-2 exhibits good oxidation stability, corrosion protection, shear stability, and pumpability in a wide array of operating conditions and temperatures.

Features and Benefits

- Excellent rust protection.
- Excellent thermal stability.
- Excellent anti-wear capacity.

Product Code

Presentation	SKU	Manufacture ID	UPC
5 Gallon Pail	UC10TO2P	UL804	810050655026
55 Gallon Drum	UC10TO2D	UL804	810050655019
265 Gallon Tote	UC10TO2T	UL804	810050655002

This product meets or exceeds the requirements of:

Caterpillar TO-2

Properties and Specifications*

Parameter	Result
Appearance	Amber, liquid
Viscosity @ 40°C, cSt, ASTM D445	37.0
Viscosity @ 100°C, cSt, ASTM D445	6.0
Viscosity index, ASTM D2270	106
Pour point, °C, ASTM D97	-30
Flash point, °C, ASTM D92	190

*Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

Revised: 03/06/2023

