

## U1P-Duty Conventional Hydraulic Oil

# SAE 30, TO-2

Industrial | United States

### Product Description

Formulated with high viscosity-index paraffinic base stocks and premium performance additives, U1P-DUTY SAE 30 Hydraulic Oil, TO-2 exhibits good oxidation stability, corrosion protection, shear stability, and pumpability in a wide array of operating conditions and temperatures.

### Features and Benefits

- Excellent rust protection.
- Excellent thermal stability.
- Excellent anti-wear capacity.

### Product Code

| Presentation    | SKU      | Manufacture ID | UPC          |
|-----------------|----------|----------------|--------------|
| 5 Gallon Pail   | UC30TO2P | UL805          | 810050655088 |
| 55 Gallon Drum  | UC30TO2D | UL805          | 810050655071 |
| 265 Gallon Tote | UC30TO2T | UL805          | 810050655064 |

This product meets or exceeds the requirements of:

Caterpillar TO-2

### Properties and Specifications\*

| Parameter                         | Result        |
|-----------------------------------|---------------|
| Appearance                        | Amber, liquid |
| Viscosity @ 40°C, cSt, ASTM D445  | 88.0          |
| Viscosity @ 100°C, cSt, ASTM D445 | 10.8          |
| Viscosity index, ASTM D2270       | 108           |
| Pour point, °C, ASTM D97          | -15           |
| Flash point, °C, ASTM D92         | 200           |

\*Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

Revised: 03/06/2023

